



Page 1/2

PRODUCT VASELINE MANUF.DATE 2023-11-24

BATCH NO. 0000408599
EXPIRY DATE 2026-11-24
DELIVERY DATE 2023-11-28

Parameter	Specification	Result
Congealing point ASTM D938	50.0 - 56.0 °C	51.5 °C
Drop Point Ph.Eur. 2.2.17/B	35.0 - 70.0 °C	57.2 °C
Cone penetr./Consistency 25 °C ASTM D937	140 - 160 1/10mm	160 1/10mm
Colour Lovibond yellow IP 17/52, mod.	0.0 - 0.5	0.3
Kin. viscosity 100 °C ASTM D7042	5.0 - 9.0 mm ² /s	6.5 mm ² /s
Reqs Ph.Eur./white soft paraf. Ph.Eur.	conforms	conforms
Limit of PAH Ph.Eur.	conforms	conforms
Identification Ph.Eur.	conforms	conforms
Characters Ph.Eur.	conforms	conforms
Acidity or Alkalinity Ph.Eur.	conforms	conforms *
Sulphated ash Ph.Eur.	0.00 - 0.05 %	< 0.05 % *
Requirements ICH CPMP/ICH/283/95	conforms	conforms *

Testmethods, marked with *, are carried out statistically.

2023-11-28

The certificate of analysis is for information only and does not warrant any particular product properties. It does not release the receiver from performing an adequate inspection of incoming shipments and the obtaining of specialist advice before using the product. The certificate of analysis does not give rise to claims of third parties to which it is provided. In addition, the most recent version of our general business condition applies.